"The classic one"



■ Corner WC-block 108 cm high for flush panels "Sigma 01/10/20/21/30/50" (Geberit®)

Art.-No. 1301.III

575,– €

Height 108 cm, Depth 22 cm, Diagonal 40 cm

With dual volume flushing technology or Start/Stop flush completely fitted for wall-hanging WC:

- adjustable in 4-stages
- with fastening material (for corner/for single-sided wall fastening)
- with sound proof set
- with sound proofing certification
- with height-adjustable feet (up to 15 cm)
- with assembly room cover below
- with moulded cistern (internal part from Geberit®) incl. cistern protection

- site protection caps
- with metre indication line
- with WC connection pipes (90°bend made of PE Ø 90/90 mm and PE adaptor Ø 90/110 mm)
- with WC connection pipes Ø 90 mm
- with WC fastening set
- actuation from the front
- without flush panel







The five major improvements to our "classic one":

- Tapped drill holes/fastening points: Now all drill holes apart from the water container! (even with one-sided wall attachments)!
- 2 Integrated, continuous, stageless wall interval regulation with simultaneous incorporation of the anchoring screw.
- 3 Integrated anti-twist protection for the assembly space cover.
- Extended assembly space cover with cutting edges/perforation for an all-over cover for tiling down to the floor!

Cross section 1: Adjusted sting wedge in original position, the block is touching the wall. The wedge is expanded, up to 2 cm if equalisation possible.

/ JA





Example of use: Corner WC-block 108 cm high, clad with Grumbach decorative panels in mint, see also page 14.

■ Flush panels for Grumbach Corner WC-blocks



Sigma 01



Sigma 10



Sigma 20/21



Sigma 30



Sigma 30 start-stop-flush



Sigma 50




Mambo

Unless otherwise stated, flush panels are **not** included in the scope of delivery of Grumbach corner WC-blocks or WC-blocks.


Installation examples

Sanitary blocks




Standard application: Corner WC-blocks 108 or 98 cm for the 90°-corner of a room

Water connection below at the front on the the left-hand side at the front



Corner WC block as a solution and fitting element for problem cases with for example "hose bathrooms".

See pictures at page 41!



Combination of corner WC-block and corner bidet block, Height 108 or 98 cm. The corner elements are connected in the factory. Please mention when ordering.

Technical data Corner WC-blocks Adjustment range height: 0-150 mm Adjustment range wall: 0-20 mm Dual volume flushing technology (can be adjusted): 4/8.5 I Factory setting: 3–4 I Small flush volume: Large flush volume: 6-8.5 I 1/2" female thread Water connection: Drain: 90°-bend made of PE \varnothing 90/90 mm and PE-adaptor $\varnothing 90/110 \text{ mm}$

