- Pre-fabricated elements for building floor-level showers
- made of extra stable Polyurethane integral rigid foam (PUR)
- can be tiled directly

Shower floor elements made of PUR
with central punctual drainage

SOUND PROTECTION TESTED!

Ultra flat and heavy duty!

Shower floor element "ultra flat" made of PUR 900 x 900 x 25 mm with central drain

Scan the code and watch the **assembly video!**

■ Shower floor element "ultra flat" made of PUR with central drainage, without drain

■ 90 x 90 cm

| Art.-No. 1803	260,– €

■ 120 x 120 cm

Art.-No. 1804	340,– €

- made of high grade, CFC-free and extra stable Polyurethane integral rigid foam (PUR)
- heat and condensation insulated
- can be tiled directly
- **with high point load capacity, therefore also suitable for wheelchairs**
- with built in 4-sided slope
- **with extra low installation height!**
- with expanded, absolutely waterproof sealing foil with overlap, therefore reliable sealing of all of the connections (Floor/Floor, Floor/Wall)
- A connecting-sealing strip for the internal corners is included in the scope of delivery (Art-No. 1894).
- square-shaped 90 x 90 cm or 120 x 120 cm
- horizontal or vertical drain, **can be ordered separately, see page 46**
- Design grates made of stainless steel are available at extra charge, see page 46.
- **Special square or rectangular shapes as well as quarter-circles and pentagonal forms up to 120 x 120 cm can be supplied on request at extra cost (80,– €, Art.-No. 1899.0)!** See order form on page 55.

Technical data

Technical data	
Dimensions	900 x 900 x 25 mm
	1200 x 1200 x 25 mm
Height of the PUR panel	25 mm
Height with drain siphon (horizontal)	75 mm without use of adjustable feet 100 mm with adjustable feet (min.) 120 mm with adjustable feet (max.) Hight of the adjustable feet: 55 mm
Drain connection	DN 40 horizontal DN 50 vertical
Drain capacity	0,7 l/s
Slope	ca. 2 %
Strength	ca. 350 kg/m^2
Density	ca. 400 kg/m^3
Tile height	8–45 mm
Inlet grate made of stainless steel	140 x 140 mm
Water sealing height	40 mm
Sealing strip overlap	50 mm

Please order separately:

The bathroom drain made of PUR, vertical or horizontal, suitable for the respective shower floor element (see page 46).

Shower floor systems

■ **Bathroom drain made of PUR vertical DN 50**

| Art.-No. 1880	85,– €

- large water sealing volume due to large sealing water container made of EPDM
- with stainless steel grate 140x140 mm. Designer grate available at extra cost, see page 47)
- with new odour trap made of hygienic EPDM
- all individual parts of the odour trap can be easily removed and cleaned

■ **Bathroom drain made of PUR horizontal DN 40**

| Art.-No. 1881	95,– €

- large water sealing volume due to large sealing water container made of EPDM
- with stainless steel grate 140x140 mm. Designer grate available at extra cost, see page 47)
- with new odour trap made of hygienic EPDM
- all individual parts of the odour trap can be easily removed and cleaned

■ **Design grate "8 x 8" made of stainless steel**

Art.-No. 1843.8x8 (extra charge)	120,– €

- as accessory for the bathroom drains made of PUR

■ **Design grate "2 x 2" made of stainless steel**

Art.-No. 1843.2x2 (extra charge)	120,– €

- as accessory for the bathroom drains made of PUR

Shower floor systems

Technical changes and errors are subject to change. Valid 06/2022

Grumbach®

Size A: [   ]

Size B: [   ]

Size A and Size B max. 120 cm

☐ **Shower floor element (PUR)**
   ☐ with central drain
      ☐ vertical   ☐ horizontal

☐ **Support frame**

☐ **Enquiry**

☐ **Order**

Size A: [   ]

Size B: [   ]

Size C: [   ]

Size D: [   ]

Size A and Size B max. 120 cm

☐ **Shower floor element (PUR)**
   ☐ with central drain
      ☐ vertical   ☐ horizontal

☐ **Support frame**

Size A: [   ]

Size B: [   ]

Size R: [   ]

Size A and Size B max. 120 cm

☐ **Shower floor element (PUR)**
   ☐ with central drain
      ☐ vertical   ☐ horizontal

☐ **Support frame**

Shower floor systems

Please note:

All Grumbach shower floor elements have a 5 cm wide **sealing foil cover.**
Through the cutting of the Grumbach shower floor element, the ends of the sloping lines no longer end in the corners of the elements. After cutting, the surrounding edge of the shower element is no longer of uniform height. This can be remedied on site with the corresponding tile adhesive.

The support frames only fit onto the Grumbach shower floor elements.

Please fill in the fields:

Sender/Stamp

Contact person

Telephone

Telefax

Date/Signature