

Fastening Bushing for water-tight passages



Fastening bushing made of PUR (black)
Heat insulated, CFC-free, with integrated rubber seal and foamed connection collar (Bitumen, PVC or special foil)




Fastening bushing made of PUR


For support rail or point fastenings with threaded bolts on flat roofs.

- Optimal for fastening bushing for photovoltaic units, air-conditioning units, ventilation etc.
- Made of extra stable PUR integral hard foam and integrated rubber seal
- Seal level in accordance with flat roof guidelines
- With poured weldable collar for every roof surface
- The water-tight bushing of threaded bolts (M10 – M12) or similar or threaded bolts, rods or pipes (\varnothing 12–50 mm) through roofs with seal.
- Available with connection collar (Bitumen, PVC or special foil, please mention when ordering).
- Incl. sealant and stainless steel sealing cuff (Art.-No. 5141 and 5143)

Installation example fastening bushing



Fastening bushing with dowl plug screwed into insulated roof. With mounted bearing rail for e.g. PV-unit or other technical roof constructions.



Dimension | Art. No.



Fastening bushing 12 made of PUR (black)
for threaded rods M10–M12
5140



Fastening bushing 30 made of PUR (black)
for threaded rods, round rods or pipes \varnothing 12–30 mm
5141



Fastening bushings 50 made of PUR (black)
for threaded rods, round rods or pipes \varnothing 30–50 mm
5143

Technical data fastening bushing

